

Technical Characteristics

purchase code : **TTI5K3**

Presentation

Product type	Three-phase Isolation transformer for generic use
Rated Power	3 KVA
Primary voltage	400 V
Secondary voltage	400 V
Connection	Δ YN
Electrostatic screen	Yes
Operating temperature	-20° +40°C
Standard	CEI EN 61558-1

Technical Characteristics

Magnetic core	made with low loss magnetic plate
Electrostatic screen	made of copper band, positioned between primary and secondary and connected to ground.
Electrical contacts	made, depending on the power, with terminals and/or bar and/or terminals.
Input voltage limits	360...440 V
Frequency limits	47.... 63 Hz
Thermal class	F
Insulation class	H
Security class	I
Insulation resistance	>10 M Ω
Altitude	1000 m
Degree of protection	IP 00
Width [mm]	300
Height [mm]	280
Depth [mm]	150
Product weight [Kg]	25



Dielectric strength	5000 V between windings for 1' at 50Hz 5000 V between windings and earth for 1' at 50Hz
Cooling	AN
Marking	CE
Type of protections	for overvoltage, overload, short circuit: provide for the insertion of specific fuses or switches
Connection	with bolts

Packaging

Package unit of measure	PCS
Number of units per package	1
height [mm]	300
width [mm]	800
depth [mm]	600
weight [kg]	45,00

Accessories

Box:	
code	C40
typology	in metal IP23 powder coated RAL
cooling	with optional fans

Warranty

12 months



INFORMATION NOTES

The information in this sheet represents the product in general, is purely indicative and cannot be used to determine the possibility of use or the reliability of the product in case of specific applications. It is the user's responsibility to perform risk assessment, as well as product evaluation and testing for specific applications.
The New C.T.A. is not responsible for the incorrect use of the information contained in this document.

Office: Via A.Scarlatti, 67 - 80129 Napoli - Italy
 Head Office: Via S. Vito, 38/39 - 80017 Melito(NA) - Italy
 Phone: (+39) 0817100925 | Email: newcta@newcta.com
 www.newcta.com

